

PINS ASSIGNMENTS

NO.	SYMBOL AND SYMBOL
1	LED+ 32 R3
2	LED+ 33 R2
3	LED- 34 R1
4	LED- 35 R0
5	GND 36 GND
6	VCDM 37 DCLK
7	DVDD 38 GND
8	MODE 39 L/R
9	DE 40 U/D
10	VS 41 VGH
11	HS 42 VGL
12	B7 43 AVDD
13	B6 44 RESET
14	B5 45 NC
15	B4 46 VCDM
16	B3 47 BITHB
17	B2 48 GND
18	B1 49 NC
19	B0 50 NC
20	G7
21	G6
22	G5
23	G4
24	G3
25	G2
26	G1
27	G0
28	R7
29	R6
30	R5
31	R4

补PI，总厚度为0.3mm

DETAIL B
SCALE 50:1

NOTES:
1. General Tolerance±0.2
2. Reference dimension.
3. Recommended cushion area should be less than nodule V.A
4. Recommended cushion adherent area TP V.A1.6mm
5. RoHS must be compliant.

TITLE	DRAWN	ME CHECKED	EE CHECKED	APPROVED	CUSTOMER'S APPROVAL
MODULE SPEC.					
DB800MIWNV01					
UNIT mm					
SCALE					
3rd Angle					
SHEET 1 OF 1					

DISPLAYBL (SZ) TECHNOLOGY CO., LIMITED